



Model created in COMSOL Multiphysics 6.4

Capillary Filling – Level Set Method

Introduction

Surface tension and wall adhesive forces are often used to transport fluid through microchannels in MEMS devices or to measure the transport and position of small amounts of fluid using micropipettes. Multiphase flow through a porous medium and droplets on solid walls are other examples where wall adhesion and surface tension strongly influence the dynamics of the flow.

This example studies a narrow vertical cylinder placed on top of a reservoir filled with water. Because of wall adhesion and surface tension at the air/water interface, water rises through the channel. The model calculates the velocity field, the pressure field, and the shape and position of the water surface.

This example demonstrates how to model the filling of a capillary channel using two multiphysics coupling features available in the Microfluidics Module. You can use either the Two-Phase Flow, Level Set or the Two-Phase Flow, Phase Field multiphysics coupling features. The Level Set interface uses a reinitialized level set method to represent the fluid interface between the air and the water. The Phase Field in Fluids interface, on the other hand, uses a Cahn–Hilliard equation, including a chemical potential to represent a diffuse interface separating the two phases. The Navier–Stokes equations are used to describe the momentum transport and the conservation of mass.

Model Definition

The model consists of a capillary channel of radius 0.15 mm attached to a water reservoir. Water can flow freely into the reservoir. Because both the channel and the reservoir are cylindrical, you can use the axisymmetric geometry illustrated in [Figure 1](#). Initially, the thin cylinder is filled with air. Wall adhesion causes water to creep up along the cylinder boundaries. The deformation of the water surface induces surface tension at the air/water interface, which in turn creates a pressure jump across the interface. The pressure variations cause water and air to move upward. The fluids continue to rise until the capillary forces are balanced by the gravity force building up as the water rises in the

channel. In the present example, the capillary forces dominate over gravity throughout the simulation. Consequently, the interface moves upward during the entire simulation.




Figure 1: Axisymmetric geometry with boundary conditions.

REPRESENTATION AND CONVECTION OF THE FLUID INTERFACE

Level Set Method

The Level Set interface automatically sets up the equations for the convection of the interface. The fluid interface is represented by the 0.5 contour of the level- set function ϕ . In air $\phi = 0$ and in water $\phi = 1$. The level-set function can thus be thought of as the volume fraction of water. The transport of the fluid interface separating the two phases is given by

$$\frac{\partial \phi}{\partial t} + \mathbf{u} \cdot \nabla \phi = \gamma \nabla \cdot \left(\epsilon \nabla \phi - \phi(1 - \phi) \frac{\nabla \phi}{|\nabla \phi|} \right)$$

The ϵ parameter determines the thickness of the interface. When stabilization is used for the level set equation, you can typically use an interface thickness of $\epsilon = h_c/2$, where h_c is the characteristic mesh size in the region passed by the interface. The γ parameter determines the amount of reinitialization. A suitable value for γ is the maximum velocity magnitude occurring in the model. The multiphysics coupling feature defines the density and viscosity according to:

$$\begin{aligned}\rho &= \rho_{\text{air}} + (\rho_{\text{water}} - \rho_{\text{air}})\phi \\ \mu &= \mu_{\text{air}} + (\mu_{\text{water}} - \mu_{\text{air}})\phi\end{aligned}$$

Due to these definitions, the density and viscosity vary smoothly across the fluid interface. The delta function is approximated by

$$\delta = 6|\phi(1 - \phi)||\nabla\phi|$$

and the interface normal is calculated from

$$\mathbf{n} = \frac{\nabla\phi}{|\nabla\phi|}$$

Phase Field Method

In the Phase Field interface the two-phase flow dynamics is governed by a Cahn–Hilliard equation. The equation tracks a diffuse interface separating the immiscible phases. The diffuse interface is defined as the region where the dimensionless phase-field variable ϕ goes from -1 to 1 . When solved in COMSOL Multiphysics, the Cahn–Hilliard equation is split up into two equations

$$\begin{aligned}\frac{\partial\phi}{\partial t} + \mathbf{u} \cdot \nabla\phi &= \nabla \cdot \frac{\gamma\lambda}{\epsilon^2} \nabla\psi \\ \psi &= -\nabla \cdot \epsilon^2 \nabla\phi + (\phi^2 - 1)\phi\end{aligned}$$

where \mathbf{u} is the fluid velocity (m/s), γ is the mobility ($\text{m}^3 \cdot \text{s} / \text{kg}$), λ is the mixing energy density (N) and ϵ (m) is the interface thickness parameter. The ψ variable is referred to as the phase-field help variable. The following equation relates the mixing energy density and the interface thickness to the surface tension coefficient:

$$\sigma = \frac{2\sqrt{2}\lambda}{3\epsilon}$$

You can typically set the interface thickness parameter to $\epsilon = h_c/2$, where h_c is the characteristic mesh size in the region passed by the interface. The mobility parameter γ determines the time scale of the Cahn–Hilliard diffusion and must be chosen judiciously. It must be large enough to retain a constant interfacial thickness but small enough so that the convective terms are not overly damped. The value $\gamma = \epsilon^2$ is usually a good initial guess. This model uses a higher mobility to obtain the correct pressure variation over the interface.

In the Phase Field interface, the volume fractions of the individual fluids are

$$V_{f1} = \frac{1-\phi}{2}, \quad V_{f2} = \frac{1+\phi}{2}$$

In the present model water is defined as Fluid 1 and air as Fluid 2.

The multiphysics coupling feature defines the density (kg/m^3) and the viscosity ($\text{Pa}\cdot\text{s}$) of the mixture to vary smoothly over the interface by letting

$$\begin{aligned} \rho &= \rho_w + (\rho_{\text{air}} - \rho_w)V_{f2} \\ \mu &= \mu_w + (\mu_{\text{air}} - \mu_w)V_{f2} \end{aligned}$$

where the single phase water properties are denoted w and the air properties air .

MASS AND MOMENTUM TRANSPORT

The Navier–Stokes equations describe the transport of mass and momentum for fluids of constant density. In order to account for capillary effects, it is crucial to include surface tension in the model. The Navier–Stokes equations are then

$$\begin{aligned} \rho \frac{\partial \mathbf{u}}{\partial t} + \rho(\mathbf{u} \cdot \nabla)\mathbf{u} &= \nabla \cdot [-p\mathbf{I} + \mu(\nabla\mathbf{u} + (\nabla\mathbf{u})^T)] + \mathbf{F}_{\text{st}} + \rho\mathbf{g} \\ \nabla \cdot \mathbf{u} &= 0 \end{aligned}$$

Here, ρ denotes the density (kg/m^3), μ equals the dynamic viscosity (Ns/m^2), \mathbf{u} represents the velocity (m/s), p denotes the pressure (Pa), and \mathbf{g} is the gravity vector (m/s^2). \mathbf{F}_{st} is the surface tension force acting at the air/water interface.

Surface Tension

In the Level Set interface the surface tension force is computed as

$$\mathbf{F}_{\text{st}} = \sigma\delta\kappa\mathbf{n}$$

Here, \mathbf{n} is the interface normal, σ is the surface tension coefficient (N/m), $\kappa = -\nabla \cdot \mathbf{n}$ is the curvature, and δ equals a Dirac delta function that is nonzero only at the fluid interface.

The following boundary force is added to enforce the contact angle:

$$\mathbf{F}_{\theta} = \sigma\delta(\mathbf{n}_{\text{wall}} \cdot \mathbf{n} - \cos\theta_w)\mathbf{n} \quad (1)$$

where θ is the contact angle (see [Figure 2](#)). If you apply a no slip boundary condition, the velocity vanishes on that boundary, and you cannot specify the contact angle. Instead, the interface remains fixed on the wall. However, if you allow a small amount of slip, it is

possible to specify the contact angle. The Wetted Wall coupling feature adds the term given by Equation 1 and consequently makes it possible to set the contact angle.

In the Phase Field interface, the diffuse interface representation makes it possible to compute the surface tension by

$$\mathbf{F}_{st} = G\nabla\phi$$

where ϕ is the phase-field parameter, and G is the chemical potential (J/m^3)

$$G = \lambda \left[-\nabla^2\phi + \frac{\phi(\phi^2 - 1)}{\epsilon^2} \right] = \frac{\lambda}{\epsilon^2}\psi$$

As seen above, the phase-field surface tension is computed as a distributed force over the interface using only ψ and the gradient of the phase-field variable. This computation avoids using the surface normal and the surface curvature, which are troublesome to represent numerically.

INITIAL CONDITIONS

Initially, the reservoir is filled with water and the capillary channel is filled with air. The initial velocity is zero.

BOUNDARY CONDITIONS

Inlet

The hydrostatic pressure, $p = \rho gz$, gives the pressure at the inflow boundary. The pressure boundary condition automatically compensates for hydrostatic pressure so the actual value for the pressure is set to zero. Only water enters through the inlet, so the volume fraction of water is 1 here.

Outlet

At the outlet, the pressure is equal to zero, that is, equal to the pressure at the top of the inflow boundary. Because it is an outflow boundary, you do not have to set any condition on the level-set function.

Wetted Walls

The Wetted Wall feature is suitable for solid walls in contact with a fluid-fluid interface. In the Level Set case, it is introduced as a multiphysics coupling feature that sets the velocity component normal to the wall to zero; that is,

$$\mathbf{u} \cdot \mathbf{n}_{\text{wall}} = 0$$

and adds a frictional boundary force

$$\mathbf{F}_{\text{fr}} = -\frac{\mu}{\beta} \mathbf{u}$$

Here, β is the slip length. The boundary condition also allows you to specify the contact angle θ , that is, the angle between the wall and the fluid interface (see [Figure 2](#)). In this example, the contact angle is 67.5° and the slip length equals the mesh element size, h .




Figure 2: Definition of the contact angle θ .

In the Phase Field simulation, one can combine the Wall feature under the Laminar Flow physics interface imposing a no slip condition for the velocity with the Wetted Wall feature under the Phase Field physics interface imposing the contact angle.

Results and Discussion

The initial development of the fluid interface is shown in [Figure 3](#). During this stage the surface changes drastically in order for it to obtain the prescribed contact angle with the wall. When this is achieved, the surface tension imposed by the surface curvature begins to pull water up through the vertical cylinder. Due to the instantaneous start, the surface oscillates slightly during the rise.




Figure 3: Snapshots of the position of the interface during the first 0.15 ms. Level Set (left) and Phase Field (right) model results.

Figure 4 shows the interface and the velocity field at three different times following the initial stage. After about 0.6 ms the shape of the water surface remains approximately constant and forms a rising concave meniscus. Comparing the velocity field in the Level Set and the Phase Field models, the Level Set results display a small velocity near the wall/

interface contact point, something that is not present in the Phase Field results. This is due to a difference in the wetted wall condition. The Level Set interface requires a wall slip length for the interface to move along the wall. As shown in Figure 4, the imposed slip velocity at the wall is small. In the Phase Field model a slip length is not necessary and the fluid velocity is truly zero on the wall.




Figure 4: Interface and velocity field at different times. Level Set (top) and Phase Field (bottom) model results.

Figure 5 shows surface plots of the pressure at $t = 0.6 \text{ ms}$. At the fluid interface there is a pressure jump of roughly 300 Pa. The jump is caused by the surface tension and forces the water and air to rise through the vertical cylinder.




Figure 5: Pressure at $t = 0.6$ ms. Level Set (top) and Phase Field (bottom) model results.

You can easily calculate the position of the interface/wall contact point by integrating the level-set function along the thin cylinder wall. Figure 6 shows the position of the contact point as a function of time. The slight oscillations of the water surface noted above are seen here also in the contact point plot. The contact plots from the Level Set and Phase Field models compare very well, except for two minor points. The surface oscillation is a bit more pronounced in the Level Set model, and the surface endpoint is somewhat higher up

in this case. Both these differences are small and are most likely related to the different implementations of the wetted wall boundary condition.




Figure 6: Position of the interface/wall contact point as a function of time. Level Set (top) and Phase Field (bottom) model result. The velocity is approximately constant after $t = 0.6$ ms.

Finally, you can verify the obtained contact angle. It is defined by $\cos\theta = \mathbf{n}^T \mathbf{n}_{\text{wall}}$. In this case, the normal to the wall is $\mathbf{n}_{\text{wall}} = \mathbf{e}_r$. The contact angle is thus $\theta = \arccos n_r$, where n_r is the radial component of the interface normal. Due to the slight oscillations of the surface, the contact angle varies during the rise. As Figure 7 shows, at $t = 0.6$ ms the contact angle is approximately 69° for the Level Set model and approximately 68° for the

Phase Field model. Both results are close to the imposed contact angle of $3\pi/8 = 1.18 \text{ rad} = 67.5^\circ$. The contact angle further approaches the imposed value if the mesh is refined.




Figure 7: Plot of $\arccos(n_r)$. At the wall, this gives the contact angle. In the Level Set model (top) the wall angle is approximately 69° and in the Phase Field model (bottom) it is approximately 68° .

Notes About the COMSOL Implementation

The model is straightforward to set up using either the Level Set or the Phase Field interface. At walls in contact with the fluid interface, you can use the Wetted Wall coupling feature for the Level Set case.


The simulation procedure consists of two steps. First the phase field and level-set functions are initialized, then the time-dependent calculation starts. This is automatically set up by COMSOL Multiphysics. You only need to specify appropriate times for the time-dependent analysis.

Application Library path: Microfluidics_Module/Two-Phase_Flow/
capillary_filling_ls




Modeling Instructions

From the **File** menu, choose **New**.

NEW

In the **New** window, click  **Model Wizard**.


MODEL WIZARD

- 1 In the **Model Wizard** window, click  **2D Axisymmetric**.
- 2 In the **Select Physics** tree, select **Fluid Flow** > **Multiphase Flow** > **Two-Phase Flow, Level Set** > **Laminar Flow**.
- 3 Click **Add**.
- 4 Click  **Study**.
- 5 In the **Select Study** tree, select **Preset Studies for Selected Multiphysics** > **Time Dependent with Phase Initialization**.
- 6 Click  **Done**.

GEOMETRY I

- 1 In the **Model Builder** window, under **Component 1 (comp1)** click **Geometry 1**.
- 2 In the **Settings** window for **Geometry**, locate the **Units** section.
- 3 From the **Length unit** list, choose **mm**.


Rectangle 1 (r1)

- 1 In the **Geometry** toolbar, click  **Rectangle**.
- 2 In the **Settings** window for **Rectangle**, locate the **Size and Shape** section.
- 3 In the **Width** text field, type 0.3.
- 4 In the **Height** text field, type 0.15.

5 Locate the **Position** section. In the **z** text field, type -0.15.

6 Click  **Build Selected**.

Rectangle 2 (r2)

1 In the **Geometry** toolbar, click  **Rectangle**.

2 In the **Settings** window for **Rectangle**, locate the **Size and Shape** section.

3 In the **Width** text field, type 0.15.

4 In the **Height** text field, type 0.5.

5 Click  **Build Selected**.

Form Union (fin)

1 In the **Model Builder** window, click **Form Union (fin)**.

2 In the **Settings** window for **Form Union/Assembly**, click  **Build Selected**.

MULTIPHYSICS

Two-Phase Flow, Level Set 1 (tpfl)

1 In the **Model Builder** window, under **Component 1 (comp1) > Multiphysics** click **Two-Phase Flow, Level Set 1 (tpfl)**.

2 In the **Settings** window for **Two-Phase Flow, Level Set**, locate the **Material Properties** section.

3 Click  **Add Multiphase Material**.

4 In the **Model Builder** window, click **Two-Phase Flow, Level Set 1 (tpfl)**.


5 Locate the **Surface Tension** section. Select the **Include surface tension force in momentum equation** checkbox.

MATERIALS

Phase 1 (mpmat1.phase1)

1 In the **Model Builder** window, under **Component 1 (comp1) > Materials > Multiphase Material 1 (mpmat1)** click **Phase 1 (mpmat1.phase1)**.

2 In the **Settings** window for **Phase**, locate the **Link Settings** section.

3 Click  **Add Material from Library**. This button is found when expanding the options next to the **Material** list.

ADD MATERIAL TO PHASE 1 (MPMAT1.PHASE1)


1 Go to the **Add Material to Phase 1 (mpmat1.phase1)** window.

2 In the tree, select **Built-in > Air**.

- 3 Click **Add Material**.

MATERIALS

Phase 2 (mpmat1.phase2)

- 1 In the **Model Builder** window, under **Component 1 (comp1) > Materials > Multiphase Material 1 (mpmat1)** click **Phase 2 (mpmat1.phase2)**.
- 2 In the **Settings** window for **Phase**, locate the **Link Settings** section.
- 3 Click  **Add Material from Library**. This button is found when expanding the options next to the **Material** list.

ADD MATERIAL TO PHASE 2 (MPMAT1.PHASE2)

- 1 Go to the **Add Material to Phase 2 (mpmat1.phase2)** window.
- 2 In the tree, select **Built-in > Water, liquid**.
- 3 Click **Add Material**.

MULTIPHYSICS

Wetted Wall 1 (ww1)

- 1 In the **Model Builder** window, under **Component 1 (comp1) > Multiphysics** click **Wetted Wall 1 (ww1)**.
- 2 Select Boundaries 6 and 7 only.
- 3 In the **Settings** window for **Wetted Wall**, locate the **Contact Angle** section.
- 4 In the θ_w text field, type $(3*\pi/8)$ [rad].

LEVEL SET (LS)

Level Set Model 1

- 1 In the **Model Builder** window, under **Component 1 (comp1) > Level Set (ls)** click **Level Set Model 1**.
- 2 In the **Settings** window for **Level Set Model**, locate the **Level Set Model** section.
- 3 In the ϵ_{ls} text field, type $5e-6$.

Initial Values, Fluid 2


- 1 In the **Model Builder** window, click **Initial Values, Fluid 2**.
- 2 Select Domain 1 only.

Add gravity volume force contribution by enabling gravity in the **Laminar Flow (spf)** interface.


LAMINAR FLOW (SPF)

- 1 In the **Model Builder** window, under **Component 1 (comp1)** click **Laminar Flow (spf)**.
- 2 In the **Settings** window for **Laminar Flow**, locate the **Physical Model** section.
- 3 Select the **Include gravity** checkbox.

Inlet 1

- 1 In the **Physics** toolbar, click  **Boundaries** and choose **Inlet**.
- 2 Select Boundary 8 only.
- 3 In the **Settings** window for **Inlet**, locate the **Boundary Condition** section.
- 4 From the list, choose **Pressure**.


LEVEL SET (LS)

- 1 In the **Model Builder** window, under **Component 1 (comp1)** click **Level Set (ls)**.
- 2 In the **Physics** toolbar, click  **Boundaries** and choose **Inlet**.
- 1 Select Boundary 8 only.
- 2 In the **Settings** window for **Inlet**, locate the **Level Set Condition** section.
- 3 From the list, choose **Fluid 2 ($\phi = 1$)**.

Outlet 1

- 1 In the **Physics** toolbar, click  **Boundaries** and choose **Outlet**.
- 2 Select Boundary 5 only.

LAMINAR FLOW (SPF)

- 1 In the **Model Builder** window, under **Component 1 (comp1)** click **Laminar Flow (spf)**.
- 2 In the **Physics** toolbar, click  **Boundaries** and choose **Outlet**.
- 1 Select Boundary 5 only.
- 2 In the **Settings** window for **Outlet**, locate the **Pressure Conditions** section.
- 3 Clear the **Compensate for hydrostatic pressure** checkbox.

Next, define a variable for the contact angle using the **Laminar Two-Phase Flow, Level Set** interface's variable for the **r** component of the interface normal, *tpf.intnormr*.

Initial Values 2


- 1 In the **Physics** toolbar, click  **Domains** and choose **Initial Values**.
- 2 Select Domain 2 only.
- 3 In the **Settings** window for **Initial Values**, locate the **Initial Values** section.

4 Clear the **Compensate for hydrostatic pressure** checkbox.

To set the correct hydrostatic pressure, the “Compensate for hydrostatic pressure” option is applied at the inlet and in the initial values node for the water-filled domain 1, but not in the initial values node for the air-filled domain 2. A warning will appear in the solver, but it can be ignored.



DEFINITIONS

Variables 1

- 1 In the **Definitions** toolbar, click  **Local Variables**.
- 2 In the **Settings** window for **Variables**, locate the **Variables** section.
- 3 In the table, enter the following settings:


Name	Expression	Unit	Description
theta	$(\text{acos}(\text{tpf1.intnormr}))[1/\text{deg}]$		Contact angle expression

Meniscus Position


- 1 In the **Definitions** toolbar, click  **Probes** and choose **Boundary Probe**.
- 2 In the **Settings** window for **Boundary Probe**, type **Meniscus Position** in the **Label** text field.
- 3 In the **Variable name** text field, type **z_pos**.
- 4 Locate the **Integration Settings** section. Clear the **Compute surface integral** checkbox.
- 5 Locate the **Source Selection** section. Click  **Clear Selection**.
- 6 Select **Boundary 6** only.
- 7 Click **Replace Expression** in the upper-right corner of the **Expression** section. From the menu, choose **Component 1 (comp1) > Level Set > Is.Vf2 - Volume fraction of fluid 2 - 1**.
- 8 Locate the **Expression** section.
- 9 Select the **Description** checkbox. In the associated text field, type **Contact point position**.
- 10 Locate the **Probe Type** section. From the **Type** list, choose **Integral**.


MESH 1

Mapped 1

In the **Mesh** toolbar, click  **Mapped**.

Size

- 1 In the **Model Builder** window, click **Size**.
- 2 In the **Settings** window for **Size**, locate the **Element Size** section.
- 3 From the **Calibrate for** list, choose **Fluid dynamics**.
- 4 From the **Predefined** list, choose **Extra fine**.
- 5 Click  **Build All**.



STUDY 1

Step 2: Time Dependent


- 1 In the **Model Builder** window, under **Study 1** click **Step 2: Time Dependent**.
- 2 In the **Settings** window for **Time Dependent**, locate the **Study Settings** section.
- 3 In the **Output times** text field, type range (0,0.25e-4, 1e-3).

Solution 1 (sol1)

- 1 In the **Study** toolbar, click  **Show Default Solver**.

The automatic time stepping can have difficulties to start when the pressure initially tries to adjust to the surface tension. A manually specified time step is therefore a more appealing option in this case.

- 2 In the **Model Builder** window, expand the **Solution 1 (sol1)** node, then click **Time-Dependent Solver 1**.

- 3 In the **Settings** window for **Time-Dependent Solver**, click to expand the **Time Stepping** section.
- 4 From the **Steps taken by solver** list, choose **Manual**.
- 5 In the **Time step** text field, type $5e-6$.
- 6 In the **Initial step fraction** text field, type $1e-3$.
- 7 In the **Study** toolbar, click  **Compute**.

The fifth default plot group shows the volume fraction of air. While the position of the air/water interface appears clearly, you can obtain an even sharper interface by plotting the 0.5 level of the same quantity using a filled contour plot, as in [Figure 3](#).

RESULTS


Contour 1

- 1 In the **Model Builder** window, expand the **Volume Fraction of Fluid 1 (Is)** node, then click **Contour 1**.
- 2 In the **Settings** window for **Contour**, locate the **Coloring and Style** section.
- 3 From the **Contour type** list, choose **Filled**.
- 4 From the **Coloring** list, choose **Color table**.
- 5 From the **Color table** list, choose **GrayScale**.
- 6 Select the **Color legend** checkbox.
- 7 From the **Legend type** list, choose **Line**.

Surface 1

- 1 In the **Model Builder** window, right-click **Surface 1** and choose **Delete**.
- 2 Click **Yes** to confirm.

Volume Fraction of Fluid 1 (Is)

- 1 In the **Model Builder** window, under **Results** click **Volume Fraction of Fluid 1 (Is)**.
- 2 In the **Settings** window for **2D Plot Group**, locate the **Data** section.
- 3 From the **Time (s)** list, choose **0**.
- 4 In the **Volume Fraction of Fluid 1 (Is)** toolbar, click  **Plot**.

Click the **Zoom Box** button in the **Graphics** toolbar, then zoom in on the lower part of the capillary. Compare the resulting plot with that in the upper-left panel of [Figure 3](#).

Reproduce the remaining plots on the left in [Figure 3](#) by plotting the solution for the time values $5e-5$, $1e-4$, and $1.5e-4$.

Velocity (spf)

The second default plot shows a surface plot of the velocity magnitude of the fluids combined with one contour lines to identify the air/water-interface. This plot can be changed to reproduce the combined velocity-field arrows and air/water-interface plot shown in [Figure 4](#).

Surface

- 1 In the **Model Builder** window, expand the **Velocity (spf)** node.
- 2 Right-click **Surface** and choose **Delete**.
- 3 Click **Yes** to confirm.



Arrow Surface 1

- 1 In the **Model Builder** window, right-click **Velocity (spf)** and choose **Arrow Surface**.
- 2 In the **Settings** window for **Arrow Surface**, locate the **Arrow Positioning** section.
- 3 Find the **z grid points** subsection. In the **Points** text field, type 30.

Contour 1

- 1 Right-click **Velocity (spf)** and choose **Contour**.
- 2 In the **Settings** window for **Contour**, locate the **Expression** section.
- 3 In the **Expression** text field, type tpf1.Vf1 .
- 4 Locate the **Levels** section. From the **Entry method** list, choose **Levels**.
- 5 In the **Levels** text field, type 0.5.
- 6 Locate the **Coloring and Style** section. From the **Coloring** list, choose **Uniform**.
- 7 From the **Color** list, choose **Gray**.

Velocity (spf)

- 1 In the **Model Builder** window, click **Velocity (spf)**.
- 2 In the **Settings** window for **2D Plot Group**, locate the **Data** section.
- 3 From the **Time (s)** list, choose **2E-4**.
- 4 In the **Velocity (spf)** toolbar, click  **Plot**.
- 5 Click the  **Zoom Extents** button in the **Graphics** toolbar.

The resulting plot should closely resemble the upper-left plot in [Figure 4](#).

Generate the remaining two plots by choosing the values $4e-4$ and $6e-4$ from the **Time** list.

Velocity, 3D (spf)

The fourth default plot group shows the air/water-interface as an isosurface plot using a revolved dataset.


Revolution 2D

- 1 In the **Model Builder** window, expand the **Results > Datasets** node, then click **Revolution 2D**.
- 2 In the **Settings** window for **Revolution 2D**, click to expand the **Revolution Layers** section.
- 3 In the **Start angle** text field, type 0.
- 4 In the **Revolution angle** text field, type 360.


Revolution 2D 1

- 1 In the **Model Builder** window, click **Revolution 2D 1**.
- 2 In the **Settings** window for **Revolution 2D**, locate the **Revolution Layers** section.
- 3 In the **Revolution angle** text field, type 230.

Edge 2D 1

- 1 In the **Results** toolbar, click  **More Datasets** and choose **Edge 2D**.
- 2 Select Boundaries 6 and 7 only.

Revolution 2D 3

- 1 In the **Results** toolbar, click  **More Datasets** and choose **Revolution 2D**.
- 2 In the **Settings** window for **Revolution 2D**, locate the **Data** section.
- 3 From the **Dataset** list, choose **Edge 2D 1**.
- 4 Locate the **Revolution Layers** section. In the **Revolution angle** text field, type 230.

Edge 2D 2


- 1 In the **Results** toolbar, click  **More Datasets** and choose **Edge 2D**.
- 2 Select Boundary 2 only.

Revolution 2D 4

- 1 In the **Results** toolbar, click  **More Datasets** and choose **Revolution 2D**.
- 2 In the **Settings** window for **Revolution 2D**, locate the **Data** section.
- 3 From the **Dataset** list, choose **Edge 2D 2**.

Volume Fraction of Fluid 1 (Is) 1


- 1 In the **Model Builder** window, expand the **Results > Volume Fraction of Fluid 1 (Is) 1** node, then click **Volume Fraction of Fluid 1 (Is) 1**.
- 2 In the **Settings** window for **3D Plot Group**, locate the **Data** section.

- 3 From the **Dataset** list, choose **Revolution 2D**.
- 4 From the **Time (s)** list, choose **3E-4**.
- 5 Locate the **Plot Settings** section. From the **View** list, choose **View 3D 2**.
- 6 Clear the **Plot dataset edges** checkbox.
- 7 In the **Volume Fraction of Fluid 1 (Is) 1** toolbar, click  **Plot**.

Isosurface 1

- 1 In the **Model Builder** window, click **Isosurface 1**.
- 2 In the **Settings** window for **Isosurface**, locate the **Coloring and Style** section.
- 3 From the **Color** list, choose **White**.

Surface 1

- 1 In the **Model Builder** window, right-click **Volume Fraction of Fluid 1 (Is) 1** and choose **Surface**.
- 2 In the **Settings** window for **Surface**, locate the **Expression** section.
- 3 In the **Expression** text field, type `1s.Vf1`.
- 4 Locate the **Coloring and Style** section. From the **Color table** list, choose **Cividis**.
- 5 Locate the **Data** section. From the **Dataset** list, choose **Revolution 2D 1**.
- 6 From the **Time (s)** list, choose **3E-4**.
- 7 In the **Volume Fraction of Fluid 1 (Is) 1** toolbar, click  **Plot**.

Surface 2


- 1 Right-click **Volume Fraction of Fluid 1 (Is) 1** and choose **Surface**.
- 2 In the **Settings** window for **Surface**, locate the **Data** section.
- 3 From the **Dataset** list, choose **Revolution 2D 3**.
- 4 Locate the **Coloring and Style** section. From the **Coloring** list, choose **Uniform**.
- 5 From the **Color** list, choose **Gray**.

Surface 3

- 1 Right-click **Volume Fraction of Fluid 1 (Is) 1** and choose **Surface**.
- 2 In the **Settings** window for **Surface**, locate the **Data** section.
- 3 From the **Dataset** list, choose **Revolution 2D 4**.
- 4 Locate the **Coloring and Style** section. From the **Coloring** list, choose **Uniform**.
- 5 From the **Color** list, choose **Gray**.

6 In the **Volume Fraction of Fluid 1 (Is) 1** toolbar, click  **Plot**.

Next, plot the pressure at $t = 0.6$ ms. Compare the result with the upper plot in [Figure 5](#).

7 Click the  **Zoom Extents** button in the **Graphics** toolbar.

Pressure (spf)

1 In the **Model Builder** window, under **Results** click **Pressure (spf)**.

2 In the **Settings** window for **2D Plot Group**, locate the **Data** section.

3 From the **Time (s)** list, choose **6E-4**.


Surface 1


1 In the **Model Builder** window, expand the **Pressure (spf)** node, then click **Surface 1**.

2 In the **Settings** window for **Surface**, locate the **Coloring and Style** section.

3 From the **Color table** list, choose **JupiterAuroraBorealis**.

4 From the **Color table transformation** list, choose **Reverse**.

5 In the **Pressure (spf)** toolbar, click  **Plot**.

6 Click the  **Zoom Extents** button in the **Graphics** toolbar.

Meniscus position

Go on to compute and plot the position of the interface/contact point.

1 In the **Model Builder** window, under **Results** right-click **Probe Plot Group 1** and choose **Rename**.

2 In the **Rename ID Plot Group** dialog, type **Meniscus position** in the **New label** text field.

3 Click **OK**.

4 In the **Settings** window for **ID Plot Group**, locate the **Legend** section.


5 Clear the **Show legends** checkbox.

6 In the **Meniscus position** toolbar, click  **Plot**.

Compare this graph with that in the upper panel of [Figure 6](#).

Finally, check the value of the contact angle at $t = 0.6$ ms ([Figure 7](#)).

2D Plot Group 7

1 In the **Results** toolbar, click  **2D Plot Group**.

2 In the **Settings** window for **2D Plot Group**, locate the **Data** section.

3 From the **Time (s)** list, choose **6E-4**.


Contour 1

- 1 Right-click **2D Plot Group 7** and choose **Contour**.
- 2 In the **Settings** window for **Contour**, locate the **Levels** section.
- 3 From the **Entry method** list, choose **Levels**.
- 4 Locate the **Expression** section. In the **Expression** text field, type `1s.Vf1`.
- 5 Locate the **Levels** section. In the **Levels** text field, type `0.5`.

Color Expression 1

- 1 Right-click **Contour 1** and choose **Color Expression**.
- 2 In the **Settings** window for **Color Expression**, click **Replace Expression** in the upper-right corner of the **Expression** section. From the menu, choose **Component 1 (comp1) > Definitions > Variables > theta - Contact angle expression - 1**.

Meniscus Angle

- 1 In the **Model Builder** window, under **Results** click **2D Plot Group 7**.
- 2 In the **Settings** window for **2D Plot Group**, type `Meniscus Angle` in the **Label** text field.
- 3 Locate the **Color Legend** section. Select the **Show maximum and minimum values** checkbox.
- 4 In the **Meniscus Angle** toolbar, click  **Plot**.

At this instance the contact angle is approximately 69 degrees, which can be found by expanding the **Range** section in the **Settings** window of the **Color Expression** node created.