



Model created in COMSOL Multiphysics 6.4

Maximizing the Buckling Load of a Diagonal Brace

Introduction

Buckling is a common failure mode for slender structures. One can distinguish between tensile and compressive modes, but it is rare to see buckling failure due to a tensile load. The buckling load can normally be increased by adding material, but oftentimes it is possible to achieve the same effect by relocating material.

Model Definition

The model studies a structural member, which provides diagonal stiffness in a larger structure. The buckling load of the member is maximized by changing two geometrical parameters, the thickness and the width. The case of a member with a length of 4 m as well as 6 m are studied. The member has a slender geometry as illustrated in [Figure 1](#).



Figure 1: The computational domain is symmetric, but this is not exploited in the model.

The member is made of steel, and the thickness is small, so its structural response can be well characterized using a shell model. The brace is put in compression using a **Rigid Connector** boundary condition with an **Applied Force** feature. The initial critical load factor and volume is first calculated and then a second study dealing with the optimization is set up.

Results

The result of the optimization for a length of 6 m is shown in [Figure 2](#). The Buckling load has been increased by 140%. The bound of the volume constraint is scaled with the brace length, so the 6 m brace is 50% heavier than the 4 m brace. This causes the optimization result for a 4 m brace to have a smaller width and larger thickness than the 6 m brace.

Lz=6 m, Lxy=0.095859 m, thickness=0.0026141 m Critical load factor=11.441 Surface: Displacement magnitud




Figure 2: The optimized 6 m member is shown for the 1st buckling mode.

Application Library path: Optimization_Module/Design_Optimization/
diagonal_brace_buckling_optimization




Modeling Instructions

From the **File** menu, choose **New**.

NEW

In the **New** window, click  **Model Wizard**.

MODEL WIZARD

- 1 In the **Model Wizard** window, click  **3D**.
- 2 In the **Select Physics** tree, select **Structural Mechanics > Shell (shell)**.
- 3 Click **Add**.
- 4 Click  **Study**.
- 5 In the **Select Study** tree, select **Preset Studies for Selected Physics Interfaces > Linear Buckling**.
- 6 Click  **Done**.

GLOBAL DEFINITIONS


Parameters 1

- 1 In the **Model Builder** window, under **Global Definitions** click **Parameters 1**.
- 2 In the **Settings** window for **Parameters**, locate the **Parameters** section.
- 3 In the table, enter the following settings:

Name	Expression	Value	Description
Lz	6[m]	6 m	Length of brace
Lxy	5[cm]	0.05 m	Brace width
thickness	5[mm]	0.005 m	Brace thickness
Lz1	3*Lxy	0.15 m	Brace end length
Rhole	Lz1/10	0.015 m	Hole radius
Fload	1[kN]	1000 N	Load

GEOMETRY 1


Block 1 (blk1)

- 1 In the **Geometry** toolbar, click  **Block**.
- 2 In the **Settings** window for **Block**, locate the **Size and Shape** section.
- 3 In the **Width** text field, type Lxy.
- 4 In the **Depth** text field, type Lxy.
- 5 In the **Height** text field, type Lz.

6 Click to expand the **Layers** section. In the table, enter the following settings:

Layer name	Thickness (m)
Layer 1	Lz1
Layer 1	Lz-2*Lz1


Boundaries to Delete

- 1 In the **Geometry** toolbar, click  **Selections** and choose **Box Selection**.
- 2 In the **Settings** window for **Box Selection**, type **Boundaries to Delete** in the **Label** text field.
- 3 Locate the **Geometric Entity Level** section. From the **Level** list, choose **Boundary**.
- 4 Locate the **Box Limits** section. In the **x minimum** text field, type $Lx \cdot 0.1$.
- 5 In the **y minimum** text field, type $Lx \cdot 0.1$.

Delete Entities 1 (del1)

- 1 In the **Model Builder** window, right-click **Geometry 1** and choose **Delete Entities**.
- 2 In the **Settings** window for **Delete Entities**, locate the **Entities or Objects to Delete** section.
- 3 From the **Selection** list, choose **Boundaries to Delete**.
- 4 Locate the **Selections of Resulting Entities** section. Select the **Resulting objects selection** checkbox.





Cylinder 1 (cyl1)

- 1 In the **Geometry** toolbar, click  **Cylinder**.
- 2 In the **Settings** window for **Cylinder**, locate the **Size and Shape** section.
- 3 In the **Radius** text field, type $Rho1e$.
- 4 In the **Height** text field, type $Rho1e$.
- 5 Locate the **Position** section. In the **x** text field, type $Lx/2$.
- 6 In the **y** text field, type $-Rho1e/2$.
- 7 In the **z** text field, type $Lz1/2$.
- 8 Locate the **Axis** section. From the **Axis type** list, choose **y-axis**.

Cylinder 2 (cyl2)


- 1 Right-click **Cylinder 1 (cyl1)** and choose **Duplicate**.
- 2 In the **Settings** window for **Cylinder**, locate the **Position** section.
- 3 In the **z** text field, type $Lz - Lz1/2$.

Difference 1 (dif1)


- 1 In the **Geometry** toolbar, click  **Booleans and Partitions** and choose **Difference**.
- 2 In the **Settings** window for **Difference**, locate the **Difference** section.
- 3 Click to select the  **Activate Selection** toggle button for **Objects to add**.
- 4 From the **Objects to add** list, choose **Delete Entities 1**.
- 5 Click to select the  **Activate Selection** toggle button for **Objects to subtract**.
- 6 Select the objects **cyl1** and **cyl2** only.
- 7 Click the  **Show Grid** button in the **Graphics** toolbar.

The geometry should now look like that in [Figure 1](#).

Internal Edges

- 1 In the **Geometry** toolbar, click  **Selections** and choose **Box Selection**.
- 2 In the **Settings** window for **Box Selection**, type **Internal Edges** in the **Label** text field.
- 3 Locate the **Geometric Entity Level** section. From the **Level** list, choose **Edge**.
- 4 Locate the **Box Limits** section. In the **z minimum** text field, type $Lz1*0.999$.
- 5 In the **z maximum** text field, type $Lz1*1.001$.
- 6 Locate the **Output Entities** section. From the **Include entity if** list, choose **Entity inside box**.

Cylinder Selection 1 (cylsel1)


- 1 In the **Geometry** toolbar, click  **Selections** and choose **Cylinder Selection**.
- 2 In the **Settings** window for **Cylinder Selection**, locate the **Geometric Entity Level** section.
- 3 From the **Level** list, choose **Edge**.
- 4 Locate the **Size and Shape** section. In the **Outer radius** text field, type $Rho1e*1.01$.
- 5 Locate the **Position** section. In the **x** text field, type $Lxy/2$.
- 6 In the **z** text field, type $Lz1/2$.
- 7 Locate the **Axis** section. From the **Axis type** list, choose **y-axis**.

Cylinder Selection 2 (cylsel2)

- 1 Right-click **Cylinder Selection 1 (cylsel1)** and choose **Duplicate**.
- 2 In the **Settings** window for **Cylinder Selection**, locate the **Position** section.
- 3 In the **z** text field, type $Lz-Lz1/2$.

ADD MATERIAL

- 1 In the **Materials** toolbar, click  **Add Material** to open the **Add Material** window.


- 2 Go to the **Add Material** window.
- 3 In the tree, select **Built-in > Structural steel**.
- 4 Click the **Add to Component** button in the window toolbar.
- 5 In the **Materials** toolbar, click  **Add Material** to close the **Add Material** window.

SHELL (SHELL)

Thickness and Offset 1

- 1 In the **Settings** window for **Thickness and Offset**, locate the **Thickness and Offset** section.
- 2 In the d_0 text field, type thickness.

Rigid Connector 1

- 1 In the **Physics** toolbar, click  **Edges** and choose **Rigid Connector**.
- 2 In the **Settings** window for **Rigid Connector**, locate the **Edge Selection** section.
- 3 From the **Selection** list, choose **Cylinder Selection 1**.
- 4 Locate the **Prescribed Displacement at Center of Rotation** section. Select the **Prescribed in x direction** checkbox.
- 5 Select the **Prescribed in y direction** checkbox.
- 6 Select the **Prescribed in z direction** checkbox.
- 7 Locate the **Prescribed Rotation** section. From the **By** list, choose **Constrained rotation**.
- 8 Select the **Constrain rotation around z-axis** checkbox.
- 9 Select the **Constrain rotation around x-axis** checkbox.

Rigid Connector 2

- 1 Right-click **Rigid Connector 1** and choose **Duplicate**.
- 2 In the **Settings** window for **Rigid Connector**, locate the **Edge Selection** section.
- 3 From the **Selection** list, choose **Cylinder Selection 2**.
- 4 Locate the **Prescribed Displacement at Center of Rotation** section. Clear the **Prescribed in z direction** checkbox.

Applied Force 1


- 1 In the **Physics** toolbar, click  **Attributes** and choose **Applied Force**.
- 2 In the **Settings** window for **Applied Force**, locate the **Applied Force** section.

3 Specify the \mathbf{F} vector as

0	x
0	y
-FLoad	z

MESH I


Edge I

- 1 In the **Mesh** toolbar, click  **More Generators** and choose **Edge**.
- 2 In the **Settings** window for **Edge**, locate the **Edge Selection** section.
- 3 From the **Selection** list, choose **Internal Edges**.

Distribution I

Right-click **Edge I** and choose **Distribution**.


Mapped I

- 1 In the **Mesh** toolbar, click  **More Generators** and choose **Mapped**.
- 2 Select Boundaries 3 and 4 only.


Distribution I

- 1 Right-click **Mapped I** and choose **Distribution**.
- 2 Select Edge 4 only.
- 3 In the **Settings** window for **Distribution**, locate the **Distribution** section.
- 4 In the **Number of elements** text field, type 20.

Free Triangular I

- 1 In the **Mesh** toolbar, click  **More Generators** and choose **Free Triangular**.
- 2 In the **Settings** window for **Free Triangular**, locate the **Boundary Selection** section.
- 3 From the **Geometric entity level** list, choose **Remaining**.

Size


- 1 In the **Model Builder** window, click **Size**.
- 2 In the **Settings** window for **Size**, locate the **Element Size** section.
- 3 From the **Predefined** list, choose **Extra fine**.
- 4 Click  **Build All**.

DEFINITIONS

Mass Properties I (mass I)


- 1 In the **Model Builder** window, under **Component 1 (comp1)** right-click **Definitions** and choose **Physics Utilities > Mass Properties**.
- 2 In the **Settings** window for **Mass Properties**, locate the **Source Selection** section.
- 3 From the **Geometric entity level** list, choose **Boundary**.
- 4 From the **Selection** list, choose **All boundaries**.
- 5 Locate the **Density** section. From the **Density source** list, choose **From physics interface**.

STUDY 1: INITIAL DESIGN


- 1 In the **Model Builder** window, click **Study 1**.
- 2 In the **Settings** window for **Study**, type Study 1: Initial Design in the **Label** text field.
- 3 In the **Study** toolbar, click  **Compute**.

RESULTS

Mass and Critical Load Factor

- 1 In the **Results** toolbar, click  **Evaluation Group**.
- 2 In the **Settings** window for **Evaluation Group**, type Mass and Critical Load Factor in the **Label** text field.

Global Evaluation I

- 1 Right-click **Mass and Critical Load Factor** and choose **Global Evaluation**.
- 2 In the **Settings** window for **Global Evaluation**, click **Add Expression** in the upper-right corner of the **Expressions** section. From the menu, choose **Component 1 (comp1) > Definitions > Mass Properties I > mass I.mass - Mass - kg**.
- 3 Click **Add Expression** in the upper-right corner of the **Expressions** section. From the menu, choose **Component 1 (comp1) > Shell > shell.LFcrit - Critical load factor**.
- 4 In the **Mass and Critical Load Factor** toolbar, click  **Evaluate**.

Mode Shape, Initial Design

- 1 In the **Model Builder** window, under **Results** click **Mode Shape (shell)**.
- 2 In the **Settings** window for **3D Plot Group**, type Mode Shape, Initial Design in the **Label** text field.



GLOBAL DEFINITIONS

Parameters 1

- 1 In the **Model Builder** window, under **Global Definitions** click **Parameters 1**.
- 2 In the **Settings** window for **Parameters**, locate the **Parameters** section.
- 3 In the table, enter the following settings:


Name	Expression	Value	Description
MO	23.5[kg]	23.5 kg	Initial Mass

ADD STUDY

- 1 In the **Home** toolbar, click  **Add Study** to open the **Add Study** window.
- 2 Go to the **Add Study** window.
- 3 Find the **Studies** subsection. In the **Select Study** tree, select **Preset Studies for Selected Physics Interfaces > Linear Buckling**.
- 4 Click the **Add Study** button in the window toolbar.
- 5 In the **Home** toolbar, click  **Add Study** to close the **Add Study** window.

STUDY 2


Parametric Sweep

- 1 In the **Study** toolbar, click  **Parametric Sweep**.
- 2 In the **Settings** window for **Parametric Sweep**, locate the **Study Settings** section.
- 3 Click **+ Add**.
- 4 In the table, enter the following settings:

Parameter name	Parameter value list	Parameter unit
Lz (Length of brace)	4 6	m

- 5 In the **Model Builder** window, click **Study 2**.
- 6 In the **Settings** window for **Study**, type Study 2: Optimization in the **Label** text field.

Parameter Optimization

- 1 In the **Study** toolbar, click  **Optimization** and choose **Parameter Optimization**.
- 2 In the **Settings** window for **Parameter Optimization**, locate the **Optimization Solver** section.
- 3 From the **Method** list, choose **COBYLA**.

4 Locate the **Objective Function** section. In the table, enter the following settings:

Expression	Description	Evaluate for
abs(comp1.shell.LFcrit)		Linear Buckling

This means that both compressive and tensile failure modes are considered.

5 From the **Type** list, choose **Maximization**.

6 From the **Solution** list, choose **Minimum of objectives**.

7 Locate the **Control Parameters** section. Click **+ Add** twice.

8 In the table, enter the following settings:

Parameter	Initial value	Lower bound	Upper bound	Unit
Lxy (Brace width)	5 [cm]	1 [cm]	20 [cm]	m
thickness (Brace thickness)	5 [mm]	1 [mm]	20 [mm]	m

9 Click **Add Expression** in the upper-right corner of the **Constraints** section. From the menu, choose **Component 1 (comp1) > Definitions > Mass Properties 1 > comp1.mass1.mass - Mass - kg**.

10 Locate the **Constraints** section. In the table, enter the following settings:

Expression	Lower bound	Upper bound	Evaluate for
comp1.mass1.mass / MO		Lz / (6 [m])	Linear Buckling


11 In the **Study** toolbar, click **= Compute**.

RESULTS

Mode Shape, Optimization

1 In the **Settings** window for **3D Plot Group**, type Mode Shape, Optimization in the **Label** text field.

2 In the **Mode Shape, Optimization** toolbar, click  **Plot**.

3 Click the  **Zoom Extents** button in the **Graphics** toolbar.

Global Evaluation 2

1 In the **Model Builder** window, under **Results > Mass and Critical Load Factor** right-click **Global Evaluation 1** and choose **Duplicate**.

2 In the **Settings** window for **Global Evaluation**, locate the **Data** section.

3 From the **Dataset** list, choose **Study 2: Optimization/Parametric Solutions 1 (sol5)**.

4 In the **Mass and Critical Load Factor** toolbar, click  **Evaluate**.

The critical load factor has been improved with a factor of 2 for the 6 m brace.

Create a new plot for the model thumbnail.

Thumbnail

1 In the **Home** toolbar, click  **Add Plot Group** and choose **3D Plot Group**.

2 In the **Settings** window for **3D Plot Group**, type Thumbnail in the **Label** text field.

3 Locate the **Data** section. From the **Dataset** list, choose **Shell**.

Surface 1

Right-click **Thumbnail** and choose **Surface**.

Deformation 1

In the **Model Builder** window, right-click **Surface 1** and choose **Deformation**.

Surface 2

1 In the **Model Builder** window, under **Results > Thumbnail** right-click **Surface 1** and choose **Duplicate**.

2 In the **Settings** window for **Surface**, locate the **Data** section.

3 From the **Dataset** list, choose **Shell 2**.

4 Click to expand the **Inherit Style** section. From the **Plot** list, choose **Surface 1**.

Line 1

1 In the **Model Builder** window, right-click **Thumbnail** and choose **Line**.

2 In the **Settings** window for **Line**, locate the **Data** section.

3 From the **Dataset** list, choose **Shell 2**.

4 Locate the **Expression** section. In the **Expression** text field, type 1.

5 Locate the **Coloring and Style** section. From the **Coloring** list, choose **Uniform**.

6 From the **Color** list, choose **Black**.

Transformation 1

1 In the **Model Builder** window, right-click **Surface 2** and choose **Transformation**.


2 In the **Settings** window for **Transformation**, locate the **Transformation** section.

3 In the **x** text field, type -0.25.

4 Clear the **Apply to dataset edges** checkbox.


5 Right-click **Transformation 1** and choose **Copy**.


Line 1

Click the  **Go to XY View** button in the **Graphics** toolbar.

Transformation 1

1 In the **Model Builder** window, right-click **Line 1** and choose **Paste Transformation**.

2 In the **Thumbnail** toolbar, click  **Plot**.

3 Click the  **Zoom Extents** button in the **Graphics** toolbar.